COMPAQ

MAILbus 400 Message Transfer Agent and Application Program Interface, Version 2.0C

Cover Letter for OpenVMS VAX

AV-QSGGE-TE

This Cover Letter lists the functional changes that have been introduced in Version 2.0C of the MAILbus™ 400 MTA. There are no functional changes that have been introduced in Version 2.0C of the MAILbus 400 Application Program Interface (API).

This Cover Letter also describes how to install Version 2.0C of the MAILbus 400 MTA and API on OpenVMS™ VAX™.

Functional Changes to the MAILbus 400 MTA

The following changes have been made to the MTA for Version 2.0C. Full details of these changes are given in the *MAILbus 400 MTA and API Release Notes for OpenVMS VAX/Alpha*.

- MTA V2.0C now supports 256 parallel agent connections.
- New MTS MSL provided
- The MTA is now supported on OpenVMS V7.2.

Installing Version 2.0C

To install this kit follow the instructions in *MAILbus 400 MTA Installing on an OpenVMS VAX System* or *MAILbus 400 API Installing on an OpenVMS VAX System* with the following exceptions:

- Make sure you install one of the following configurations of prerequisite software:
  - — OpenVMS V6.2
    DECnet™/OSI® for OpenVMS V6.3 with ECO8
    DIGITAL™ X.500 Directory Service for OpenVMS (Base component) V3.0 (or later)
  - — OpenVMS V7.1
    DECnet-Plus for OpenVMS V7.1 with ECO2, including the DECnet Application Interface component (formerly known as the OSI Applications Kernel or OSAK™)
    DIGITAL X.500 Directory Service for OpenVMS (Base component) V3.0 (or later)
  - — OpenVMS V7.2
    DECnet-Plus for OpenVMS V7.2, including the DECnet Application Interface component (formerly known as the OSI Applications Kernel or OSAK™, V3.0-003O
    DIGITAL X.500 Directory Service for OpenVMS (Base component) V3.0 (or later)

- The approximate disk space required on the system disk (in blocks) during and after installation for the different components are shown in the following table:

Component Title	Space Required (in blocks)	
	During	After
MAILbus 400 MTA Mgt	3700	1400
MAILbus 400 MTA Base	3500	2700
MAILbus 400 MTA Server, Mgt, and Base	19800	17800
MAILbus 400 API and Base	3500	3100

- Note that Version 2.0C is no longer distributed on 9-track 1600 BPI Magtape or TK50 Streaming Tape. It is only available as part of the DIGITAL CD-ROM Software Library for OpenVMS VAX Layered Products. This means the installation instructions are different from those in Version 2.0.

  From the SYSTEM account on the node or cluster where you want to install a MAILbus 400 MTA component or the API, mount the CD-ROM as follows:

  ```
  $ MOUNT device-name volume-label
  ```

  where ***device-name*** and ***volume-label*** are as specified in the *OpenVMS Layered Products Compact Disk User's Guide*. The MTA and API files are located on the CD-ROM in the directory named MTAC020.

- The command to install either the MTA or the API is:

  ```
  $ @SYS$UPDATE:VMSINSTAL MTAC020 device-name:[MTAC020] OPTIONS N
  ```

The image identification of the new images in this kit is MTA V2.0C-150.

The version number of the kit when displayed using NCL management is V2.0.150.

Compaq Computer Corporation makes no representations that the use of its products in the manner described in this publication will not infringe on existing or future patent rights, nor do the descriptions contained in this publication imply the granting of licenses to make, use, or sell equipment or software in accordance with the description.

The following are trademarks of Compaq Computer Corporation: DECnet, DIGITAL, MAILbus, OpenVMS, OSAK, VAX, and the COMPAQ logo.

OSI is a registered trademark of CA Management, Inc.

© Compaq Computer Corporation 1995,1998,1999. All rights reserved.