System Support Addendum

PRODUCT NAME: CDA Converter Library for OpenVMS Version 2.2 **SSA 31.31.03-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX™:

VAX 4000 Model 100,
VAX 4000 Model 200,
VAX 4000 Model 300,
VAX 4000 Model 400,
VAX 4000 Model 500,
VAX 4000 Model 600

VAX 6000™ Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series,
VAX 6000 Model 600 Series

VAX 7000 Model 600 Series

VAX 8200™, VAX 8250™, VAX 8300™,
VAX 8350™, VAX 8500™, VAX 8530™,
VAX 8550™, VAX 8600™, VAX 8650,
VAX 8700, VAX 8800, VAX 8810,
VAX 8820™, VAX 8830, VAX 8840,

VAX 9000™ Model 110,
VAX 9000 Model 210,
VAX 9000 Model 300 Series,
VAX 9000 Model 400 Series

VAX 10000 Model 600 Series

VAXft™ Model 110,
VAXft Model 310,
VAXft Model 410,
VAXft Model 610,
VAXft Model 612

VAX–11/730, VAX–11/750™,
VAX–11/780™, VAX–11/785

MicroVAX™:

MicroVAX II™, MicroVAX 2000,
MicroVAX 3100 Model 10, 10E
MicroVAX 3100 Model 20, 20E
MicroVAX 3100 Model 30,
MicroVAX 3100 Model 40,
MicroVAX 3100 Model 80,
MicroVAX 3100 Model 90,
MicroVAX 3300, MicroVAX 3400,
MicroVAX 3500, MicroVAX 3600,
MicroVAX 3800, MicroVAX 3900

VAXstation™:

VAXstation II, VAXstation 2000,
VAXstation 3100 Model 30,
VAXstation 3100 Model 38,
VAXstation 3100 Model 40,
VAXstation 3100 Model 48,
VAXstation 3100 Model 76,
VAXstation 3200, VAXstation 3500,
VAXstation 3520, VAXstation 3540

VAXstation 4000 VLC™,
VAXstation 4000 Model 60,
VAXstation 4000 Model 90,

VAXserver™:

VAXserver 3100, VAXserver 3300,
VAXserver 3400, VAXserver 3500,
VAXserver 3600, VAXserver 3602,
VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 200,
VAXserver 4000 Model 300,
VAXserver 4000 Model 500

VAXserver 6000 Model 210,
VAXserver 6000 Model 220,
VAXserver 6000 Model 310,
VAXserver 6000 Model 320,
VAXserver 6000 Model 410,
VAXserver 6000 Model 420,
VAXserver 6000 Model 510,
VAXserver 6000 Model 520,
VAXserver 6000 Model 610,
VAXserver 6000 Model 620,
VAXserver 6000 Model 630

digital™

December 1993
AE-NJ74D-TE

Processors Not Supported

MicroVAX I™, VAXstation I, VAX–11/725, VAX–11/782, VAXstation 8000.

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Disk Space Requirements (Block Cluster Size = 1)

Disk space required for installation:	43,000 blocks
Disk space required for use (permanent):	16,500 blocks

These counts refer to the disk space required on the system disk if you do not have the CDA™ Run-Time Services already installed. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

OPTIONAL HARDWARE

If the DEC GKS™ runtime system is installed, the Graphics Hardcopy converter can be used to generate the Color and Monochrome Sixel formats and the Hewlett-Packard® Graphics Language (HP-GL®) format. For a list of output devices supporting those formats, refer to the DEC GKS for OpenVMS™ Software Product Description (SPD 26.20.xx).

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster™ configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI™, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

The CDA Converter Library V2.2 requires the following:

- OpenVMS Operating System V5.0
- DECimage™ Application Services V2.0 or Version 3.0 (when using TIFF or MacPaint® converters)
- DEC GKS V4.2 for OpenVMS (Runtime System - when using the Graphics Hardcopy converter)
- Digital's Image Applications Services (DAS) V3.0 or later - when using the Graphics Hardcopy converter. DAS V3.0 is distributed as part of the Motif kit.

Note: A version of CDA Run-Time Services is supplied with the Converter Library kit, but DECwindows™ non-Motif® systems cannot run CDA Run-Time Services V1.0.

For Workstations Running DECwindows V1.0 prior to Motif

The Converter Library installation procedure will not update your CDA Base Services software, if you are running a pre-Motif version of DECwindows. Digital™ recommends that you upgrade your system to a Motif version of DECwindows. The CDA Converter Library V2.2 is not warranted to run under older versions of CDA. However, if you have a pre-Motif version of DECwindows and cannot upgrade, it is possible that the performance of the CDA Converter Library V2.2 will be adequate to your needs.

OpenVMS Tailoring

The following OpenVMS classes are required for full functionality of this layered product running standalone:

- OpenVMS Required Saveset
- Utilities

For more information on OpenVMS classes and tailoring, refer to the OpenVMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

DEC GKS V4.2 for OpenVMS (Runtime System)

Note: If the DEC GKS runtime system is installed, the DDIF Graphics Hardcopy converter can be used to generate the HP-GL, Color Sixel, ReGIS™, PostScript® and Monochrome Sixel formats. Refer to the DEC GKS for OpenVMS Software Product Description (SPD 26.20.xx) for a list of output devices that support these formats. If the DEC GKS development or runtime system is not installed, the Graphics Hardcopy converter will not function.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements of the current version.

DISTRIBUTION MEDIA

9-track 1600 BPI Magtape, TK50 Streaming Tape.

This product is also available as part of the OpenVMS Consolidated Software Distribution on CD-ROM.

ORDERING INFORMATION

Software Licenses: QL-VZAA*-**
Software Media: QA-VZAA*-**
Software Documentation: QA-VZAAA-GZ
Software Product Services: QT-VZAA*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The ordering information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

© Digital Equipment Corporation 1989, 1993. All rights reserved.

® Hewlett-Packard and HP-GL are registered trademarks of Hewlett-Packard Company.

® MacPaint is a registered trademark of Claris Corporation.

® Motif is a registered trademark of the Open Software Foundation, Inc.

® PostScript is a registered trademark of Adobe Systems Inc.

All other trademarks and registered trademarks are the property of their respective owners.

™ CDA, CI, DEC, DEC GKS, DECimage, DECwindows, Digital, MicroVAX, MicroVAX I, MicroVAX II, OpenVMS, ReGIS, VAX, VAX–11/750, VAX–11/780, VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8820, VAX 9000, VAXft, VAXcluster VAXserver VAXstation, VAXstation 4000 VLC, and the DIGITAL Logo, are trademarks of Digital Equipment Corporation.